

MATERIAL SAFETY DATA SHEET

May be used to comply with OSHA's Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.	HMIS HAZARD RATING			
SAFETEC OF AMERICA	HEALTH	0	0 = INSIGNIFICANT	3 = HIGH
	FLAMMABILITY	1	1 = SLIGHT	4 = EXTREME
	REACTIVITY	0	2 = MODERATE	
TRANSPORTATION INFORMATION				
PROPER SHIPPING NAME	Not Regulated		REF.	Not Applicable
HAZARD CLASS / PKG. GRP.	None / None		LABEL	None Required
IDENTIFICATION NUMBER	None			

SECTION 1 - PRODUCT / COMPANY IDENTIFICATION

IDENTITY (AS USED ON LABEL AND LIST)	Page 1 of 2
Petro Lock™	
MANUFACTURER'S NAME Safetec of America, Inc.	EMERGENCY TELEPHONE NUMBER (24 Hours) (800) 255-3924
ADDRESS (NUMBER, STREET, P.O. BOX) 887 Kensington Avenue @ William L. Gaiter Pkwy.	TELEPHONE NUMBER FOR INFORMATION (716) 895-1822
(CITY, STATE AND ZIP CODE) Buffalo, NY 14215	DATE PREPARED September 1, 2004 SUPERSEDES February 20, 2002

SECTION 2 - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

HAZARDOUS COMPONENTS (SPECIFIC CHEMICAL IDENTITY; COMMON NAME(S))	CAS #	% (wt.) (OPTIONAL)	OSHA PEL/STEL		ACGIH TLV/TWA/STEL	
			PPM	MG/M ³	PPM	MG/M ³
Block Copolymer, mixture; CAS proprietary		> 99	None Established		None Established	

This product is not known to contain a substance subject to Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR 372 at or above minimal amounts.

SECTION 3 - HEALTH HAZARD DATA

ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EXPOSURE	EMERGENCY AND FIRST AID PROCEDURES
EYES: Product is practically non-irritating to the eyes.	Flush eyes with clear running water for a minimum of 15 minutes while holding eyelids open; if irritation persists, seek medical attention.
SKIN: Product is non-irritating to the skin.	NOT ordinarily required.
INGESTION: This product is generally considered to have a low order of acute oral toxicity.	NOT ordinarily required.
INHALATION: Product is not expected to cause irritation to the nose, throat or respiratory tract.	NOT ordinarily required.
HEALTH HAZARDS (ACUTE AND CHRONIC): This product is not considered a health hazard.	
CARCINOGENICITY	NTP? No IARC MONOGRAPHS? No OSHA REGULATED? No
No additional information	
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Preexisting eye, skin, or breathing disorders may become aggravated through exposure.	

MATERIAL SAFETY DATA SHEET

IDENTITY (AS USED ON LABEL AND LIST)

Petro Lock™

Page 2 of 2

Date: September 1, 2004

SECTION 4 - FIRE FIGHTING MEASURES

FLASH POINT (METHOD USED)

Not Applicable

FLAMMABLE LIMITS (% Volume in Air for Lowest Flashing Component)

LEL: Not Applicable

UEL: Not Applicable

EXTINGUISHING MEDIA

Water fog, Dry chemicals, Foam, CO₂

SPECIAL FIRE FIGHTING PROCEDURES

DO NOT enter confined fire space without full bunker gear (Helmet with face shield, bunker coats, gloves and rubber boots. Wear NIOSH/MSHA approved self contained breathing apparatus. Cool fire exposed containers with water.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS

Material will not burn unless preheated. Product can accumulate static charges when handled. Thermal decomposition may emit toxic and irritating substances.

SECTION 5 - PRECAUTIONS FOR SAFE HANDLING AND USE / LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS SPILLED OR RELEASED

In case of accidental spills, provide adequate ventilation; avoid generating dust. Sweep up material or vacuum (using HEPA filter equipped system) if possible to avoid generating airborne dust. Place spilled material into a clean, dry container for disposal.

WASTE DISPOSAL METHODS

Dispose of in accordance with Local, State, and Federal regulations. Products classified 5.2aust. Sw